

## **CWDM Lite™ OADM Multiplexer**

Completely passive CWDM optical add/drop multiplexer. Add or drop 1 to 4 CWDM channels in either direction, all other CWDM channels pass through. Available as dual fiber or single fiber unit.

- Housed in 1-RMU (1.75 in height) shelf
- Rack Mountable in 19" or 23" racks
- Simple to install, requires no configuration
- · Completely passive, no power required, no cooling
- Low insertion loss high isolation
- Disassembles easily for cleaning
- Fully Universal (bidirectional operation on any port)
- Operating Temperature -5° to +70° C

- Fully transparent for all protocols
- Accepts any data rate and any protocol on any port up to 10 Gbps, also 40 Gbps (DPSK, DQPSK)
- High reliability, MTBF > 50 yrs
- Telcordia GR-1209 and GR1221 qualified
- ISO 9001 manufacturing
- 1-4 channel optical add / drop CWDM multiplexer (Specify channels to be dropped in PO)

#### **Applications**

- Any equipment using ITU-T transceivers
- SONET/SDH OC-3 to OC-768, STM-1 to STM-256
- Routers and Switches with optical CWDM interfaces
- GBIC, SFP, & XFP

- Xenpak
- · Ethernet over fiber
- ATM over fiber
- · and many more...

### CWDM Lite™ 1-Channel OADM, Single Fiber or Dual Fiber **Specifications** Insertion Loss ea (max) 1.6 dB Throughput Loss (max) 1 1 dB **Product Code** TCAD-01CH-01/02-xx-cc CWDM Lite™ 2-Channel OADM, Single Fiber or Dual Fiber **Specifications** Insertion Loss ea (max) 1.9 dB Throughput Loss (max) 1.5 dB TCAD-02CH-01/02-xx-yy-cc **Product Code** CWDM Lite™ 4-Channel OADM, Single Fiber or Dual Fiber **Specifications** 2 7 dB Insertion Loss ea (max) Throughput Loss (max) 1.2 dB **Product Code** TCAD-04CH-01/02-xx-yy-cc

### Single Fiber CWDM Lite™ 1 Channel OADM




# Single Fiber CWDM Lite™ 2 Channel OADM



# Single Fiber CWDM Lite™ 4 Channel OADM



# CWDM OPTICAL ADD/DROP MODULE



#### Notes

- <u>kx</u> First Avail. Wavelength: ITU Grid Channel #
- yy Last Avail. Wavelength: ITU Grid Channel #
- cc LCU: Ultra Polish dual LC

SCU: Ultra Polish SC \*may not be available FCU: Ultra Polish FC \*may not be available

For more information or a quote, call a Customer Representative at 1.888.250.1562